

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,906,747 B2
APPLICATION NO. : 09/913062
DATED : June 14, 2005
INVENTOR(S) : Sadami Okada

Page 1 of 9

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

IN THE SPECIFICATION:

Column 2, line 32, change "solid" to --fixed--;

Column 6, line 5, delete current paragraph and insert therefor:


--The CPU 19 outputs the raw data in which the gradation has been thus restored to a monitor display unit 22 and another signal processing system (S14 in Fig. 3).--;

IN THE DRAWINGS:

Please replace the drawings with the attached Replacement Formal Drawings.
Figs. 1-8

Signed and Sealed this

Tenth Day of October, 2006

A handwritten signature in black ink, appearing to read "Jon W. Dudas". The signature is stylized with a large, looping initial "J" and a distinct "D".

JON W. DUDAS
Director of the United States Patent and Trademark Office

U.S. Patent

Jun. 14, 2005

Sheet 1 of 8

6,906,747 B2

FIG. 1




FIG. 2
ACTIONS DURING IMAGE SHOOTING





FIG. 3
ACTIONS DURING PLAYBACK




U.S. Patent

Jun. 14, 2005

Sheet 3 of 8

6,906,747 B2

FIG. 4




U.S. Patent

Jun. 14, 2005

Sheet 4 of 8

6,906,747 B2

FIG. 5

EFFICACY OF REDUCING GRADATION
JUMPING IN INPUT RANGE [0-6]

U.S. Patent

Jun. 14, 2005

Sheet 5 of 8

6,906,747 B2




FIG. 6

U.S. Patent

Jun. 14, 2005

Sheet 6 of 8

6,906,747 B2

FIG. 7

EFFICACY OF EQUALIZING NOISE AMPLITUDE IN INPUT RANGE [108-4095]





FIG. 8



U.S. Patent

Jun. 14, 2005

Sheet 8 of 8

6,906,747 B2

FIG. 9

